

202AA



Specification

Application:

Suitable for the suction and delivery of mild chemicals and effluent in general industrial and agricultural applications.

Technical Description:

Inner Tube: Black EPDM.

Reinforcement: High tensile textile cords with embedded steel helix wire.

Cover: Black EPDM.

Temperature Range: -40°C to +120°C

Advantages:

- Abrasion and ozone resistant cover.
- Suitable for use in applications up to 10 Bar.

PRODUCT CODE	ID mm	OD mm	Working Pressure Bar	Bursting Pressure Bar	Bending Radius mm	Weight kg/m	Coil Length m
BWSD125	25	35	10	30	100	0.69	30.5 - 61*
BWSD132	32	42	10	30	128	0.82	30.5 - 61*
BWSD138	38	48	10	30	152	0.95	30.5 - 61*
BWSD151	51	61	10	30	204	1.24	6.1 - 30.5 - 61*
BWSD163	63	75	10	30	252	1.78	30.5 - 61*
BWSD176	76	88	10	30	304	2.14	6.1 - 30.5 - 61*
BWSD1102	102	114	10	30	408	3.01	6.1 - 30.5 - 61*
BWSD1115	115	127	10	30	460	3.34	30.5 - 61*
BWSD1127	127	141	10	30	635	4.73	6.1 - 30.5 - 61*
BWSD1152	152	166	10	25	760	5.96	6.1 - 30.5 - 61*
BWSD1203	203	221	10	25	1015	9.81	6.1 - 30.5 - 61*
BWSD1254	254	272	10	25	1270	13.43	6.1 - 30.5

Specifications can be subject to change; data is correct at the time of production. Please contact the sales office for specific enquiries.