

## Alfa-jet 210 Pressure Wash Hose



### Specification

Tube: oil, detergents and hot water resistant synthetic rubber. Reinforcement: one high tensile steel braid.

Cover: abrasion, ozone and hydrocarbon resistant blue synthetic rubber, pin-pricked.  
Black cover also available.

Application: high pressure power cleaners.  
Specially designed for hot water applications.  
Not recommended for steam service.  
Length: random  
DH SCAN crimp short code: A 210

Item Code	ID (Dash)	ID (mm)	ID (in)	OD (mm)	OD (in)	WP (Mpa)	WP (psi)	BP (Mpa)	BP (psi)	BR (mm)	BR (in)	Weight (kg/m)	Weight (lb/ft)
1000192	4	6,0	1/4"	12,1	0,48	21,0	3000	84,0	12000	50	1,97	0,161	0,11
1000185	5	8,0	5/16"	14,1	0,56	21,0	3000	84,0	12000	60	2,36	0,184	0,13
1000098	6	10,0	3/8"	15,6	0,61	21,0	3000	73,0	10588	65	2,56	0,250	0,17
1000166	8	13,0	1/2"	19,5	0,77	21,0	3000	73,0	10588	90	3,54	0,359	0,25

Kiowa is not liable for the use or applications that differs from what is confirmed in their technical catalogue, product sheets, offers, order confirmations and recommendations contained in them.