

Compressed Air



195AT

Compressed air 20 bar (300 psi) - Polyurethane - Pneumatic tools

Tube: black polyurethane/PVC - oil mist resistant.

Reinforcement: high tensile textile cords.

Cover: light blue synthetic elastomer - abrasion and ozone resistant.

Application: compressed air.

Specially designed for pneumatic tools and paint spray.

Constant operation: -20 °C +60 °C (-4 °F +140 °F)

↔		↔		↻		↻		⤴		⚠	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	10,00	0,39	20	300	60	900	24,0	0,94		0,065	0,05
8,0	5/16"	12,00	0,47	20	300	60	900	32,0	1,26		0,080	0,06
10,0	3/8"	15,00	0,59	20	300	60	900	40,0	1,57		0,115	0,08
13,0	1/2"	19,00	0,75	20	300	60	900	52,0	2,05		0,185	0,13
16,0	5/8"	23,00	0,91	20	300	60	900	64,0	2,52		0,260	0,18
19,0	3/4"	26,00	1,02	20	300	60	900	76,0	2,99		0,305	0,21
25,0	1"	33,00	1,30	20	300	60	900	100,0	3,94		0,450	0,31

Specifications can be subject to change; data is correct at the time of production. Please contact the sales office for specific enquiries.