

Petrochemical/Oil



655AA

**Fuel-oil delivery 16 bar (240 psi)
exceeds EN 1761 - TRbF 131/2**

Tube: black conductive NBR.

Reinforcement: high tensile textile cords.

Cover: black conductive CR - abrasion, ozone, hydrocarbon and fire resistant.

Application: fuel and oil delivery.

Designed for long service life in heavy duty applications.

Constant operation: -30 °C +70 °C (-22 °F +158 °F)

↔		↔		⊙		⊙		⌒		⌒		⌒	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
19,0	3/4"	31,00	1,22	16	240	48	720	125,0	4,92		0,560	0,38	
25,0	1"	37,00	1,46	16	240	48	720	150,0	5,91		0,690	0,47	
32,0	1 1/4"	44,00	1,73	16	240	48	720	175,0	6,89		0,870	0,59	
38,0	1 1/2"	51,00	2,01	16	240	48	720	225,0	8,86		1,020	0,69	
51,0	2"	67,00	2,64	16	240	48	720	275,0	10,83		1,550	1,05	
63,0	2 1/2"	79,00	3,11	16	240	48	720	300,0	11,81		1,880	1,27	
76,0	3"	92,00	3,62	16	240	48	720	350,0	13,78		2,310	1,56	
102,0	4"	118,00	4,65	16	240	48	720	450,0	17,72		3,410	2,30	
152,0	6"	170,00	6,69	16	240	48	720	750,0	29,53		5,140	3,46	

Specifications can be subject to change; data is correct at the time of production. Please contact the sales office for specific enquiries.