

## Flexopak 2SC Hydraulic Hose



### Specification

#### Application:

Suitable for high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water.

#### Technical Description:

**Inner Tube:** Oil resistant synthetic rubber.

**Reinforcement:** Two high tensile steel braids.

**Cover:** Abrasion, ozone and hydrocarbon resistant synthetic rubber.

**Temperature Range:** -40°C to +100°C.

**Standard / Approval:** ISO 11237 - EN 857 2SC.

**Length:** Random.

#### Advantages:

- Abrasion, ozone and hydrocarbon resistant synthetic rubber cover.
- Halogen free.

PRODUCT CODE	ID			OD		WORKING PRESSURE		MIN. BURSTING PRESSURE		MIN. BENDING RADIUS	WEIGHT
	-size	mm	Ins	mm	Ins	PSI	Bar	PSI	Bar	mm	kg/m
1000365	-04	06	1/4	13.0	0.51	5850	400	23200	1600	75	0.255
1000366	-05	08	5/16	14.7	0.58	5000	350	20000	1400	85	0.300
1000367	-06	10	3/8	16.5	0.65	4800	330	19200	1320	90	0.370
1000368	-08	13	1/2	19.9	0.78	4000	275	16000	1100	130	0.470
1000369	-10	16	5/8	23.4	0.92	3630	250	14500	1000	170	0.596
1000370	-12	19	3/4	27.6	1.09	3120	215	12500	860	200	0.789
1000371	-16	25	1	34.9	1.37	2400	165	9600	660	250	1.155

Specifications can be subject to change; data is correct at the time of production. Please contact the sales office for specific enquiries.