

KIOWA



ALFAGOMMA GROUP

// SEWERJET EVOLUTION



// SEWERJET EVOLUTION

The hose has a multi textile braids cord construction that makes it an highly innovative and reliable product designed to meet the ever changing market demands.

- Specifically engineered for high-pressure water jetting and sewer flushing, clearing blocked drains and culverts.
- The high tensile textile braid reinforcements ensure the hose has ultra-high flexibility even at low temperatures (-30 °C): bend radius is greatly reduced especially when compared to standard products currently available in the market.
- Compact and lightweight construction offers easier handling and improved jetting performance providing longer service life.
- The new smooth, extra high abrasion resistant cover is made to withstand constant dragging, offering an overall improvement in efficiency of operation.
- New SEWERJET EVO is the ideal solution for Vacuum Trucks OEM's and operators. Utility companies and Drainage Contractors who all need a reliable, flexible and durable product for all their sewer jetting applications.



// SEWERJET EVO

**Sewer hose 250 bar (3625 psi) - Textile braids**

Tube: oil, detergents and hot water resistant synthetic rubber.

Reinforcement: two and three high tensile textile braids. **Cover:** smooth. Abrasion, ozone and very low sliding resistance black synthetic rubber.

Application: sewer jetting and heavy duty, high pressure water cleaning; extremely flexible.

Temperature: -30 °C +80 °C (-22 °F +176 °F)

Length: tolerance ± 1% (norm ISO 1307).

Notes: a dedicated fittings range ensures high safety level.

Hose can be supplied assembled with BSP female / BSP male in fixed lengths, pressure tested according to EN 10204 3.1 B.

Item Code	Constr.	ID (Dash)	ID (mm)	ID (in)	OD (mm)	OD (in)	WP (Mpa)	WP (psi)	BP (Mpa)	BP (psi)	BR (mm)	BR (in)	Weight (kg/m)	Weight (lb/ft)	Length (m)
1004972	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	40,000
1003959	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	60,000
1003837	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	80,000
1004082	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	100,000
1003979	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	120,000
1003764	2TB	12	19,0	3/4"	31,5	1,24	25,0	3630	62,5	9050	90	3,54	0,600	0,41	80,000
1003663	2TB	12	19,0	3/4"	31,5	1,24	25,0	3630	62,5	9050	90	3,54	0,600	0,41	100,000
1003980	2TB	12	19,0	3/4"	31,5	1,24	25,0	3630	62,5	9050	90	3,54	0,600	0,41	120,000
1003738	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	80,000
1003609	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	100,000
1003736	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	120,000
1005837	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	150,000
1005939	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	160,000
1005873	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	200,000
1005920	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	80,000
1005921	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	100,000
1005916	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	120,000
1005922	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	150,000
1005923	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	200,000

ALFAGOMMA SEWERJET EVO // MINETUFF // -12 3/4" (DN 19) WP 250 bar 8K2AA MADE IN ITALY

// NO SKIVE FERRULE FOR MULTISPIRAL AND STANDARD FITTINGS

Hose	Table n°	-08 DN 12 1/2"	-12 DN 19 3/4"	-16 DN 25 1"	-20 DN 32 1 1/4"
SEWERJET EVO	271	H1200FK0	H1200FK0	H1200FK0	H1200FK0
			H1300FK0	H1300FK0	